

DATA SHEET

1.	Manufacturer		DEUTRUCK
2.	Type	Model designation	EFG 10
3.	Carrying capacity	Q	t 10
4.	Load centre	C	mm 600
5.	Type of drive	Diesel, petrol, l.p. gas	electric
6.	Operator type	stand on / driver seated	driver seated
7.	Tyre	C=cushion, P=pneumatic, SE=solid	SE
8.	Wheels (x = driven)	number front / rear	4 x / 2
9.	Lift	h3 standard lift height	mm 3.300
10.	Lift	h2 standard free lift	mm 100
11.	Lift	h5 special free lift	mm -
12.	Fork	Length x width x thickness	mm 1.200 x 200 x 80
13.	Tilt angle	Forward a backwards b	(°) 3/8
14.	Dimensions	L2 Length with fork thickness	mm 3.590
15.	Dimensions	B Width	mm 2.140
16.	Dimensions	h1 Mast standard lowered	mm 2.665
17.	Dimensions	h4 Mast standard extended	mm 4.300
18.	Turning radius	Wa Outer	mm 3.550
19.	Load distance	x from center or front axle	mm 680
20.	Aisle for 90° stacking		mm 5.240 / 5.640
21.	Stability factor	DIN standard 15138 (F.E.M.)	Yes
22.	Speeds	Travel laden / unladen	km / h 10 / 12
23.	Speeds	Lift laden / unladen	m / s 0,15 / 0,20
24.	Speeds	Lower laden / unladen	m / s 0,35 / 0,25
25.	Drawbar pull	At the hook laden / unladen	daN 2.000
26.	Gradeability	Laden / unladen	% 7 / 12
27.	Weight of truck	with battery	kg 13.500
28.	Axle loadings	unladen front / rear	kg 5.800 / 7.700
29.	Axle loadings	laden front / rear	kg 21.347 / 2.153
30.	Tyres	No. front / rear	4 / 2
31.	Tyres	dimensions front	“ or mm 8.25-20
32.	Tyres	dimensions rear	“ or mm 8.25-15
33.	Wheel base	Y	mm 2.320
34.	Track width	front wheels axle	mm 1.620
35.	Ground clearance	m1 at the deepest point	mm 200
36.	(laden)	m2 at center of wheelbase	mm 230
37.	Brakes	Service brake	hydr.
38.	Brakes	Parking brake	mech.
39.	Battery	Type	
40.	Battery	Volt / Ah cap.	V / Ah 96 / 920 – 1.250
41.	Electric motors	drive motor	kW 27
42.	Electric motors	lifting motor	kW 24
43.	I.C.engine	Manufacturer / type	
44.	I.C.engine	Continous output to DIN 6270	R.P.M.
45.	I.C.engine	At engine speed (DIN 6270)	kW
46.	I.C.engine	Fuel consumption	l / h
47.	I.C.engine	Strokes / no. of cyl / cap	(cm3)
48.	Clutch		Hydr.
49.	Speed control		electronic
50.			
51.	Drive axle		
52.	Operating pressure		bar 150

*valid for standard version as per VDI 2198 – modifications without pre-notice
version 12/2007