

DATA SHEET

1.	Manufacturer		DEUTRUCK
2.	Type	Model designation	EFG 1,25
3.	Carrying capacity	Q t	1,25
4.	Load centre	C mm	500
5.	Type of drive	Electric, diesel, gas	electric
6.	Operator type	stand on / driver seated	driver seated
7.	Tyre	C=cushion, P=pneumatic	P / P
8.	Wheels (x = driven)	number front / rear	2 / 1 x
9.	Lift	h3 standard lift height mm	2.300 to 6.500
10.	Lift	h2 standard free lift mm	150 to 2.250
11.	Lift	h5 special free lift mm	-
12.	Fork	Length x width x thickness mm	1.000 x 100 x 35
13.	Tilt angle	Forward a backwards b)°	7 / 7
14.	Dimensions	L2 Length with fork thickness mm	1.736
15.	Dimensions	B Width mm	988
16.	Dimensions	h1 Mast standard lowered mm	2.000
17.	Dimensions	h4 Mast standard extended mm	3.550
18.	Turning radius	WA outer mm	1.399
19.	Load distance	x from centre or front axle mm	335
20.	Aisle for 90° stacking	mm	3.065 / 3.187
21.	Stability factor	DIN standard 15138 (F.E.M.)	Yes
22.	Speeds	Travel laden / unladen km / h	11,5 / 12,5
23.	Speeds	Lift laden / unladen m / s	0,30 / 0,50
24.	Speeds	Lower laden / unladen m / s	0,58 / 0,60
25.	Drawbar pull	At the hook laden / unladen N	1.120 / 1.370 max. 4.370 / 4.640
26.	Gradeability	Laden / unladen %	4,0 / 6,7 max. 11 / 17
27.	Weight of truck	incl. battery kg	2.730
28.	Axle loadings	unladen front / rear kg	1.200 / 1.530
29.	Axle loadings	laden front / rear kg	3.410 / 570
30.	Tyres	No. front / rear	2 / 1
31.	Tyres	dimensions front “ or mm	18 x 7 – 8
32.	Tyres	dimensions rear “ or mm	18 x 7 – 8
33.	Wheel base	y mm	1.146
34.	Track width	centre wheels front / rear mm	838 / -
35.	Ground clearance	m1 at the deepest point mm	90
36.	(laden)	m2 at centre of wheelbase mm	100
37.	Brakes	Service brake	hydr.
38.	Brakes	Parking brake	Mech.
39.	Battery	Type	43535A
40.	Battery	Volt / Ah cap. (55 hrs. rate) V / Ah	24 / 500 to 800
41.	Electric motors	drive motor kW	4,0
42.	Electric motors	lifting motor kW	7,6
43.	I.C.engine	Manufacturer / type	
44.	I.C.engine	Continuous output to DIN 6270 R.P.M.	
45.	I.C.engine	At engine speed (DIN 6270) kW	
46.	I.C.engine	Fuel consumption l / h	
47.	I.C.engine	Strokes / no. of cyl / cap (cm3)	
48.	Clutch		
49.	Speed control		electronic
50.			
51.	Drive axle		
52.	Operating pressure	N	185

*valid for standard version as per VDI 2198 – subject to modification without notice