

## DATA SHEET

1.	Manufacturer		DEUTRUCK
2.	Type	Model designation	EFG 2,5
3.	Carrying capacity	Q	t 2,5
4.	Load centre	C	mm 500
5.	Type of drive	Diesel, petrol, l.p. gas;electric	electric
6.	Operator type	stand on / driver seated	driver seated
7.	Tyre	C=cushion, P=pneumatic	SE/SE
8.	Wheels (driven)	number front / rear	2x / 2
9.	Lift	h3 standard lift height	mm 2.900 – 7.000
10.		h2 standard free lift	mm 150 – 2.130
11.		h5 special free lift	mm -
12.	Fork	Length x width x thickness	mm 1.000 x 100 x 40
13.	Tilt angle	Forward a backwards b	(°) 6 / 8
14.	Dimensions	L2 Length with fork thickness	mm 2.242
15.		B Width	mm 1.163
16.	Mast	h1 Mast standard lowered	mm 2.215
17.		h4 Mast standard extended	mm 3.696
18.	Turning radius	Wa Outer	mm 2.193
19.	Load distance	x from center or front axle	mm 425
20.	Aisle for 90° stacking		mm 3.980
21.	Stability factor	DIN standard 15138 (F.E.M.)	Yes
22.	Speeds	Travel laden / unladen	km / h 21 / 18
23.		Lift laden / unladen	m / s 0,46 / 0,60
24.		Lower laden / unladen	m / s 0,58 / 0,56
25.	Drawbar pull	At the hook laden / unladen	daN 2.700 / 12.200
26.	Gradeability	Laden / unladen	% 8 / 13,5
27.	Weight of truck		kg 4.600
28.	Axle loadings	unladen front / rear	kg 2.530 / 2.220
29.		laden front / rear	kg 6.400 / 850
30.	Tyres	No. front / rear	2 / 2
31.		dimensions front	“ or mm 23 x 9 - 10
32.	s	dimensions rear	“ or mm 200/50-10
33.	Wheel base	Y	mm 1.525
34.	Track width	center wheels front / rear	mm 955 / 920
35.	Ground clearance	m1 at the deepest point	mm 140
36.	(laden)	m2 at center of wheelbase	mm 125
37.	Brakes	Service brake	hydr.
38.		Parking brake	mechanic
39.	Battery	Type	PZS,DIN 43 536 A
40.	Capacity		V / Ah 80 / 480-775
41.	Electric motors	drive motor	kW 18
42.		lifting motor	kW 21
43.	Speed control	electronic	AC
44.	Noise level		db (A) 66
45.	Operating pressure		N 160

\*valid for standard version as per VDI 2198 - subject to modification without prior notice

06/2023

