

TECHNICAL DATA SHEET

1.	Manufacturer		DEUTRUCK
2.	Type	model designation	EFG 7
3.	Capacity	Q	kg 6.000
4.	Load centre	c	mm 600
5.	Type of drive	electr. , diesel, LPG	battery
6.	Operator type	handoperated, stand on, driver seated	driver seated
7.	Tyre	C = cushion / P = pneumatic / SE = super elastic	SE
8.	Wheels (x=driven)	number front/rear	2/2
9.	Lift	h3 standard lift height	mm 3.300
10.		h2 standard free lift	mm 0
11.		h5 special free lift	mm
12.	Forks	length x width x thickness	mm 1.200 x 150 x 60
13.	Fork carriage	FEM 4A	yes
14.	Fork carriage width	b3	Mm 1.400
15.	Tilting	forward / backward	(°)
16.	Dimensions	l1 length with forks	mm 4.340
17.		l2 length without forks	mm 3.290
18.		b1 overall width	mm 1.530
19.		h1 mast standard lowered	mm 2.750
20.		h4 mast standard extended	mm 4.400
21.		h6 height of overhead guard	mm 2.450
22.		h7 seat height	mm 1.350
23.	Turning radius	Wa or WA'	mm 2.840
24.	Load distance	x = centre of drive axle to fork	mm 580
25.	Aisle width for 90° stacking	1.000 x 1.200 pallets	mm 4.820
26.	Stability	DIN 15138 (FEM)	
27.	Speeds	travel laden/unladen	km/h 12 / 14
28.		lift laden/unladen	m / s 0,22 / 0,28
29.		lower laden/unladen	m / s 0,35 / 0,30
30.	Drawbar pull	at the hook laden/unladen	N 1.300
31.	Grade ability	laden	% 15 / 20
32.	Weight of truck		kg 11.370
33.	Axle loading	unlade front / rear	kg 6.380 / 4.990
34.		laden front / rear	kg 15.598 / 1.722
35.	Wheels (x=driven)	number front / rear	2 / 2
36.	Tyres	dimensions front	" or mm 3.55 / 65-15
37.		dimensions rear	" or mm 23x9-10
38.	Wheelbase	y	mm 2.200
39.	Tread front / rear	b 10 / b 11	mm -
40.	Ground clearance	m1 under mast laden	mm 180
41.		m2 centre of wheelbase	mm 220
42.	Brakes	service brake	hydraulic
43.		parking brake	
44.	Battery	type	iron clad battery
45.		Volt / Ah cap.	80 / 1.085
46.	Electric motors	Drive motor	kW 2x 12,5
47.		Lifting motor	kW 26
48.	Tow coupling		
49.	Transmission	torque converter	AC electronic
50.	Gear change	forward / backward	
51.	Sound level	in drivers ear	db(A) 85
52.	Operating pressure		bar 210

according to VDI 2198 - standard version - subject to modification without pre-advice

Version : 09/2018

EFG 7

