

## DATA SHEET

1.	Manufacturer		<b>DEUTRUCK</b>
2.	Type	Model designation	EGU 3000
3.	Carrying capacity	Q	t 3
4.	Load centre	C	mm 600
5.	Type of drive	Diesel, petrol, l.p. gas	electric
6.	Operator type	stand on / driver seated	pedestrian
7.	Tyre	C=cushion, P=pneumatic	PU/Vulkollan
8.	Wheels (driven)	number front / rear	3 – 1x / 4
9.	Lift	h3 standard lift height	mm 130
10.	Load height	h13 lowered height	mm 90
11.	Load height	l1 length	mm 1.990
12.	Load height	b2 / b1	mm 690 / 790
13.	Load height	h14 height of shaft	mm 810 / 1.270
14.	Dimensions	l2 length up to forks	mm 770 / 840
15.	Dimensions	b5 distance of forks/width over forks	mm 330 / 670
16.	Forks	s/e/l	mm 60 / 170 / 1.150
17.	Load distance	x	mm 970
18.	Turning radius	Wa	mm 2.080
19.	Aisle for 90° stacking	Ast pallet 1.000 x 1.200	mm 2.250
20.	Speeds	Travel speed with / without load	km / h 5.0 / 6.0
21.	Speeds	Lift time with / without load	m / s 0.042 / 0.061
22.	Speeds	Lower time with / without load	m / s 0.068 / 0.055
23.	max. Gradeability	with / without load	% 5 / 20
24.	Weight	incl. battery	kg 770
25.	Axle loadings	with load front / rear	kg 1.502 / 2.352
26.	Axle loadings	without load front / rear	kg 698 / 208
27.	Tyres	Dimensions front	“ or mm 230 x 70
28.	Tyres	Dimensions rear	“ or mm 85 x 85
29.	Tyres	additional tyres	“ or mm 100 x 40
30.	Wheel base	Y lowered / lifted	mm 1.670 7 1.570
31.	Track width	s front / rear	370
32.	Ground clearance	m2 at center of wheelbase	mm 35
33.	Electric motors	drive motor	kW 1,5
34.	Electric motors	lifting motor	kW 2,0
35.	Brakes	Service brake / parking brake	Electric
36.	Brakes	mec. / hydr. / electr.	Electric
37.	Battery	V / AH	V / AH 24/230 - 375
38.	Battery	type	PZS
39.	Battery	weight	kg 220
40.	Clutch		
41.	Speed control		
42.	Noise level	at ear of driver	dB
43.	Drive axle		
44.	Operating pressure		N

\*valid for standard version as per VDI 2198

Version: 02 / 2008

