



DATA SHEET

1.	Manufacturer		DEUTRUCK
2.	Type	Model designation	EGU S 2000
3.	Carrying capacity	Q	t 2
4.	Load centre	C	mm 600
5.	Type of drive	Diesel, petrol, l.p. gas	electric (battery)
6.	Operator type	stand on / driver seated	foldable platform
7.	Tyre	C=cushion, P=pneumatic, PU = polyurethane	PU
8.	Wheels (driven)	number front / rear	1 x + 2/2
9.	Lift	h3 standard lift height	mm 125
10.	Load height	h13 lowered height	mm 85
11.	Load height	l1 length	mm 1.870/2.300
12.	Load height	b1/b2 width above cap	mm 800
13.	Load height	h14 height of shaft	mm 830/1.280
14.	Dimensions	l2 length incl. fork	mm 1870
15.	Dimensions	b5 distance of forks	mm 540/680
16.	Forks	ISO 2331	mm 1.150 x 170 x 64
17.	Load distance	x	mm 965
18.	Turning radius	Wa walking/standing	mm 1.778/2.233
19.	Aisle for 90° stacking	Pallet 800 x 1200	mm 2.213/2.213
20.	Speeds	Travel speed with/without load	km/h 9/9,5
21.	Speeds	Lift speed with/without load	m/s 0,05/0,065
22.	Speeds	Lower speed with/without load	m/s 0,06/0,08
23.	Gradeability	with/without load	% 10/16
24.	max. Gradeability	with/without load	% 10/16
25.	Weight	incl. battery	kg 894
26.	Axle loadings	with load front/rear	kg 1.485/1.292
27.	Axle loadings	without load front/rear	kg 189/588
28.	Tyres	Dimensions front/rear	“ or mm 250 x 100/4 x 85 x 95
29.	Wheel base	y	mm 1.370
30.	Track width	b10 front/b11 rear	mm 570/390
31.	Ground clearance	m2 at center of truck min./max.	mm 25/150
32.	Electric motors	drive motor	kW 2,2
33.	Electric motors	lifting motor	kW 2,2
34.	Brakes	Service brake/parking brake	electric
35.	Brakes	mechanic/hydraulic./electric	electromagnetic
36.	Battery	V/Ah	V/Ah 24/150 – 300 Ah
37.	Battery	type	PzS / PzB
38.	Battery	weight	kg 270
39.	Speed control		Electronic AC
40.	Noise level	at driver's ear	dB 70

*valid for standard version as per VDI 2198, modification without prior notice

