

## DATA SHEET

1.	Manufacturer		<b>DEUTRUCK</b>
2.	Type	model designation	EGV 1.25S
3.	Carrying capacity	Q	t 1,25
4.	Load centre	C	mm 600
5.	Type of drive	diesel, electr.	electric
6.	Operator type	stand on / driver seated	pedestrian controlled
7.	Tyre	C = cushion, P = pneumatic, SE = super-elastic, PU = polyurethane	VU
8.	Wheels (x = driven)	number front / rear	1 x + 1 / 2
9.	Lift	h3 standard lift height	mm 3.200
10.		h2 standard free lift	mm 80
11.		h5 special free lift	mm
12.	Fork	length x width x height	mm 1.150 x 200 x 70
13.	Tilt angle	forwards a backwards b	(°)
14.	Dimensions	L2 length without forks	mm 765
15.		B width	mm 870
16.		h1 mast standard lowered	mm 2.100
17.		h4 mast standard extended	mm 3.634
18.	Turning radius	Wa	mm 1.495
19.	Load distance	x from centre or front axle	mm 693
20.	Aisle for 90° stacking	DIN 1.000 x 1.200 mm	mm 2.200
21.	Stability factor	DIN standard 15138 (F.E.M.)	yes
22.	Speeds	travel laden / unladen	km / h 5/6
23.		lift laden / unladen	m / s 0,13 / 0,20
24.		lower laden / unladen	m / s adjustable
25.	Drawbar pull	at the hook laden / unladen	N
26.	Gradeability	laden	% 10/14
27.	Weight of truck		kg 1.150
28.	Axle loadings	unladen front / rear	kg on request
29.		laden front / rear	kg on request
30.	Tyres	number front / rear	4/2
31.		dimensions front	“ or mm 250
32.		dimensions rear	“ or mm 85
33.	Wheel base	y	mm 1.250
34.	Track width	b10/b11 centre wheels front / rear	mm
35.	Ground clearance	m1 at the deepest point	mm
36.		m2 at centre of wheelbase	mm 30
37.	Brakes	service brake	electric
38.	Brakes	parking brake	deadman brake
39.	Battery		
40.		capacity	V / Ah 24V / 150-270Ah
41.	Electric motor	drive motor	kW 1
42.		lift motor	kW 2,5
43.	Noise level	in driver's ear	dB 68
44.	Transmission		
45.	Hydr. pressure		N

