

DATA SHEET

1.	Manufacturer		DEUTRUCK
2.	Type	model designation	EGV 1200
3.	Carrying capacity	Q	t 1,2
4.	Load centre	C	mm 600
5.	Type of drive	diesel, electr.	electric
6.	Operator type	stand on / driver seated	Pedestrian controlled
7.	Tyre	C = cushion, P = pneumatic, SE = super-elastic, PU = polyurethane	PU
8.	Wheels (x = driven)	number front / rear	1 x + 1 / 2
9.	Lift	h3 standard lift height	mm 2.500 – 5.500
10.		h2 standard free lift	mm 0 – 2.200
11.		h5 special free lift	mm
12.	Fork	length x width x thickness	mm 1.160 x 180 x 65
13.	Tilt angle	forwards a backwards b	(°)
14.	Dimensions	L2 length with fork thickness	mm 755
15.		B width	mm 800
16.		h1 mast standard lowered	mm
17.		h4 mast standard extended	mm
18.	Turning radius	Wa	mm 1.546
19.	Load distance	x from centre or front axle	mm
20.	Aisle for 90° stacking	DIN 1.000 x 1.200 mm	mm 2.398
21.	Stability factor	DIN standard 15138 (F.E.M.)	
22.	Speeds	travel laden / unladen	km / h 6,0 / 5,5
23.		lift laden / unladen	m / s 0,18 / 0,12
24.		lower laden / unladen	m / s 0,25 / 0,30
25.	Drawbar pull	at the hook laden / unladen	N
26.	Gradeability	laden	% 10 / 7
27.	Weight of truck	incl. battery	kg 960
28.	Axle loadings	unladen front / rear	kg 670 / 290
29.		laden front / rear	kg 740 / 1.420
30.	Tyres	number front / rear	1x + 1 / 2
31.		dimensions front	“ or mm 230 x 75
32.		dimensions rear	“ or mm 85 x 100
33.	Wheel base	y	mm 1.315
34.	Track width	b10/b11 centre wheels front / rear	mm 514 / 398
35.	Ground clearance	m1 at the deepest point	mm 30
36.	(laden)	m2 at centre of wheelbase	mm 30
37.	Brakes	service brake	electro-magnetic
38.	Brakes	parking brake	
39.	Battery		DIN 43535 B
40.		capacity	V / Ah 24V / 250Ah
41.	Electric motor	drive motor	kW 1,2
42.		lift motor	kW 2
43.	I.C. engine	manufacturer / type	kW
44.		continues output to ISO 1585	R.P.M.
45.		at engine speed (ISO 1585)	KW.
46.		fuel consumption	l / h
47.		strokes / no. of cyl / cap	(cm ³)
48.	Speed control		
49.	Noise level	in driver's ear	dB <70
50.	Transmission		
51.	Drive axle		
52.	Hydr. pressure		N

