

## DATA SHEET

1.	Manufacturer		DEUTRUCK
2.	Type	Model designation	EGV-ST 1350
3.	Carrying capacity	Q	t 1,35
4.	Load centre	C	mm 600
5.	Type of drive	Diesel, petrol, l.p. gas	electric
6.	Operator type	stand on / driver seated	driver seated
7.	Tyre	C=cushion, P=pneumatic	Tractotan/Tandem
8.	Wheels (driven)	number front / rear	1 x + 2/2
9.	Lift	h3 standard lift height	mm 5.500
10.	Lift	h2 standard free lift	mm 1.960
11.	Lift	h5 special free lift	mm -
12.	Fork	Length x width x thickness	mm 70/170/1.150
13.	Tilt angle	Forward a backwards b	(°)
14.	Dimensions	L2 Length with fork thickness	mm 910
15.	Dimensions	B Width	mm 557
16.	Dimensions	h1 Mast standard lowered	mm 2.390
17.	Dimensions	h4 Mast standard extended	mm 5.330
18.	Turning radius	Wa Outer	mm 1.558
19.	Load distance	x from center or front axle	mm
20.	Aisle for 90° stacking		mm -/2.452
21.	Stability factor	DIN standard 15138 (F.E.M.)	
22.	Speeds	Travel laden / unladen	km / h 12/12
23.	Speeds	Lift laden / unladen	m / s 0,32 / 0,17
24.	Speeds	Lower laden / unladen	m / s 0,22 / 0,41
25.	Drawbar pull	At the hook laden / unladen	N
26.	Gradeability	Laden / unladen	% 7/5
27.	Weight of truck		kg 1.495
28.	Axle loadings	unladen front / rear	kg 455 / 1.040
29.	Axle loadings	laden front / rear	kg 1.737 / 1.108
30.	Tyres	No. front / rear	1 x + 2/2
31.	Tyres	dimensions front	“ or mm 255 x 125
32.	Tyres	dimensions rear	“ or mm 4 x 85x 70
33.	Wheel base	Y	mm
34.	Track width	center wheels front / rear	mm
35.	Ground clearance	m1 at the deepest point	mm
36.	(laden)	m2 at center of wheelbase	mm 10/25
37.	Brakes	Service brake	electric
38.	Brakes	Parking brake	
39.	Battery	Type	
40.	Battery	Volt / Ah cap. (55 hrs. rate)	V / AH 24 / 465
41.	Electric motors	drive motor	kW 3 AC
42.	Electric motors	lifting motor	kW 3 AC
43.	I.C.engine	Manufacturer / type	
44.	I.C.engine	Continous output to DIN 6270	R.P.M.
45.	I.C.engine	At engine speed (DIN 6270)	kW
46.	I.C.engine	Fuel consumption	l / h
47.	I.C.engine	Strokes / no. of cyl / cap	(cm3)
48.	Clutch		
49.	Speed control		electronic
50.	Noise level		dB (A) < 70
51.	Drive axle		
52.	Operating pressure		N

\*valid for standard version as per VDI 2198

Version 12/2015

